

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Date of issue: 17-2-2015 Revision date: 17-2-2015 Supersedes: 17-2-2015 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Eurol Ultrance PSA 0W-30

Product code : E100018
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Main use category : industrial use, professional use, consumer use

Use of the substance/mixture : Lubricant

Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Eurol bv.
Energiestraat 12
P.O. Box P.O. Box 135
7442 DA Nijverdal - The Netherlands
T +31 548 615165
r.hilgers@eurol.com - www.eurol.com

1.4. Emergency telephone number

Emergency number : +31 548 615165

(Monday to Friday: 8:00 - 17:00)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements (CLP) : P102 - Keep out of reach of children.

EUH-statements : EUH210 - Safety data sheet available on request.

Child-resistant fastening : Not applicable
Tactile warning : Not applicable

2.3. Other hazards

Other hazards not contributing to the

classification

: This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classified as T/R45: May cause cancer" (Note L).". USED ENGINE OILS: Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

26-2-2018 EN (English) 1/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 3: Composition/information on ingredients

Substances

Not applicable

3.2. **Mixtures**

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1-Decene, homopolymer, hydrogenated	(CAS-No.) 68037-01-4 (EC-No.) 500-183-1 (REACH-no) 01-2119486452-34	35 - 50	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy paraffinic	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	25 - 35	Asp. Tox. 1, H304
Mineral Oil		3 - 5	Asp. Tox. 1, H304
Reaction products of Benzeneaminephenyl- with nonene (branched) phenyl- with nonene (branched)	(CAS-No.) 36878-20-3 (EC-No.) 253-249-4 (REACH-no) 01-2119488911-28	1 - 3	Aquatic Chronic 4, H413
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	(CAS-No.) 125643-61-0 (EC-No.) 406-040-9 (REACH-no) 01-2119878226-29	1 - 3	Aquatic Chronic 4, H413

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1.	Description	of first aid	magailrag
4.1.	Describitor	OF HISLAID	measures

First-aid measures general

: Seek medical attention if ill effect develops.

First-aid measures after inhalation

Take victim to fresh air, in a quiet place, in an half laying position and if necessary take medical advice. Allow the victim to rest.

First-aid measures after skin contact

Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. High-pressure injection under skin may cause serious damage. Seek medical attention if ill effect or irritation develops.

First-aid measures after eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Ensure adequate flushing of eyes by separating eyelids with the fingers. Obtain medical attention if pain, blinking, tears or redness persist.

First-aid measures after ingestion

Consult a doctor/medical service if you feel unwell. If vomiting occurs spontaneously, keep head below the hips to prevent aspiration. Do not induce vomiting.

Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation

: At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.

Symptoms/effects after skin contact

: Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Symptoms/effects after eye contact Symptoms/effects after ingestion

Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.

Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.

Symptoms/effects upon intravenous administration

· Unknown

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. **Extinguishing media**

Suitable extinguishing media : Carbon dioxide (CO2), dry chemical powder, foam. Water fog.

Unsuitable extinguishing media : Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special hazards arising from the substance or mixture

: Combustion generates: CO, CO2, POx, NOx, SOx, H2S. Fire hazard

Explosion hazard : Not expected to be a fire/explosion hazard under normal conditions of use.

Advice for firefighters

Precautionary measures fire : Do not enter fire area without proper protective equipment, including respiratory protection.

Firefighting instructions : Use water spray or fog for cooling exposed containers.

26-2-2018 EN (English) 2/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Protection during firefighting

: Use self-contained breathing apparatus and chemically protective clothing

Other information

: Prevent fire fighting water from entering the environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and public

6.1.1. For non-emergency personnel

Protective equipment

: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Use protective clothing.

Emergency procedures

: Consider evacuation.

6.1.2. For emergency responders

Protective equipment

: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Emergency procedures

: No specific measures are necessary.

6.2. Environmental precautions

Dike for recovery or absorb with appropriate material. Notify authorities if product enters sewers or public waters. Prevent soil and water pollution. Prevent liquid from entering sewers, watercourses, underground or low areas. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

6.3. Methods and material for containment and cleaning up

For containment

: Large quantities: Contain large spillage with sand or earth.

Methods for cleaning up

: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Take up large spills with pump or vacuum and finish with dry chemical absorbent.

Other information

: Use suitable disposal containers. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations. On water, recover/skim from surface and pour out in disposal container.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

Precautions for safe handling

: Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes.

Hygiene measures

Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep container tightly closed and in well ventilated place.

Storage conditions : Store in original container.

Incompatible products : Reacts vigorously with strong oxidizers and acids.

Maximum storage period : 5 year Storage temperature : \leq 40 °C

Information on mixed storage : Keep away from : oxidizing materials. strong acids.

Storage area : Store at ambient temperature.

Special rules on packaging : Keep container tightly closed and dry.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

26-2-2018 EN (English) 3/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Exposure-value for oil mist : 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours).

8.2. Exposure controls

Appropriate engineering controls:

Large quantities: Contain large spillage with sand or earth.

Personal protective equipment:

Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed.

Materials for protective clothing:

PVC gloves. Neoprene or nitrile rubber gloves

Hand protection:

In case of repeated or prolonged contact wear gloves. The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream). The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Eye protection:

Eye protection should only be necessary where liquid could be splashed or sprayed

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use. Avoid repeated or prolonged skin contact. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Equipment should conform to EN 166.

Respiratory protection:

Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn. Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.

Personal protective equipment symbol(s):





Environmental exposure controls:

See Heading 12. See Heading 6.

Consumer exposure controls:

PVC gloves. Neoprene or nitrile rubber gloves.

Other information:

Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : liquid
Appearance : liquid. Oily.
Colour : Brown.
Odour : characteristic.
Odour threshold : no data available
pH : no data available

Relative evaporation rate (butylacetate=1) : < 0,1

Melting point : -45 °C ASTM D 97
Freezing point : no data available
Boiling point : > 280 °C
Flash point : 185 °C
Auto-ignition temperature : > 240 °C
Decomposition temperature : no data available

26-2-2018 EN (English) 4/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Flammability (solid, gas) : no data available

Vapour Pressure 20°C : < 0,1 hPa

Relative vapour density at 20 °C : > 1 (air=1)

Relative density : no data available

Density : 0,84 kg/l

Solubility : insoluble in water.

Log Pow : > 3

Viscosity, kinematic : 80 - 120 cSt

Viscosity, dynamic : no data available

Explosive properties : no data available

Oxidising properties : no data available

Explosive limits : 0,6 - 7 vol %

9.2. Other information

VOC content : 0 %

Other properties : Gas/vapour heavier than air at 20'C.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

Moisture. Overheating.

10.5. Incompatible materials

Strong oxidizing agents. strong acids.

10.6. Hazardous decomposition products

CO, CO2, POx, NOx, SOx, H2S.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Reaction products of Benzeneaminephenyl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3)	
LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rat	> 2000 ml/kg (OECD 402 method)

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
LD50 oral rat	> 2000 mg/kg (OECD 401 method)
LD50 dermal rat	> 2000 ml/kg (OECD 402 method)

1-Decene, homopolymer, hydrogenated (68037-01-4)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 ml/kg
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 5,2 mg/l/4h

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 inhalation rat (mg/l)	> 5,53 mg/l

 Skin corrosion/irritation
 : Not classified

 Serious eye damage/irritation
 : Not classified

 Respiratory or skin sensitisation
 : Not classified

 Germ cell mutagenicity
 : Not classified

 Carcinogenicity
 : Not classified

26-2-2018 EN (English) 5/8

Safety Data Sheet

Reproductive toxicity

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU	FU) 2015/830
--	--------------

: Not classified

STOT-single evangure : Not classified

STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Eurol Ultrance PSA 0W-30

Viscosity, kinematic 80 - 120 mm²/s

Other information : Toxicological data have not been determined specifically for this product. Information given is

based on a knowledge of the components and the toxicology of similar products. Likely route of

exposure: ingestion, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Ecotoxicological data have not been determined specifically for this product. Information given

is based on a knowledge of the components and the ecotoxicology of similar products.

Ecology - water : This product floats on water and may affect the oxygen-balance in the water.

Acute aquatic toxicity : Not classified Chronic aquatic toxicity : Not classified

Reaction products of Benzeneaminephenyl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3)	
LC50 fish 1	> 100 mg/l 96h; Brachydanio rerio (zebra-fish)
EC50 Daphnia 1	> 100 mg/l EC50 48h - Daphnia magna [mg/l]
EC50 72h algae (1)	600 mg/l
ErC50 (algae)	> 100 mg/l 72h; Desmodesmus subspicauts

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
LC50 fish 1	> 74 mg/l Brachydanio rerio (zebra-fish)
EC50 Daphnia 1	> 100 mg/l EC50 24h - Daphnia magna [mg/l]
EC50 72h algae (1)	> 3 mg/l Desmodesmus subspicatus
ErC50 (algae)	> 3 mg/l 72h; Desmodesmus subsicatus

()	•
Mineral Oil	
LC50 fish 1	> 100 mg/l Pimephales promelas
EC50 Daphnia 1	> 10000 mg/l
EC50 72h algae (1)	> 100 mg/l Scenedesmus quadricauda

1-Decene, homopolymer, hydrogenated (68037-01-4)	
LC50 fish 1	> 1000 mg/l Oncorhynchus mykiss (Rainbow trout)
LC50 fish 2	> 750 mg/l Pimephales promelas
EC50 Daphnia 1	190 mg/l EC50 48h - Daphnia magna [mg/l]
EC50 72h algae (1)	1000 mg/l Scenedesmus capricornutum

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 fish 1	100 mg/l
EC50 Daphnia 1	10000 mg/l

12.2. Persistence and degradability

Eurol Ultrance PSA 0W-30		
Persistence and degradability	Not readily biodegradable.	

Biodegradation 0 % Sturm - 28 days

Mineral Oil

Biodegradation 31 % OECD TG 301 B

1-Decene, homopolymer, hydrogenated (68037-01-4)

Persistence and degradability Not readily biodegradable

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Biodegradation 31 %

12.3. Bioaccumulative potential

Eurol Ultrance PSA 0W-30	
Log Pow	> 3
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.

26-2-2018 EN (English) 6/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Reaction products of Benzeneaminephenyl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3)				
Bioconcentration factor (BCF REACH)	1584,89			
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)				
Bioconcentration factor (BCF REACH)	260 (OECD 305 method)			
Log Pow	9,2			
1-Decene, homopolymer, hydrogenated (680	37-01-4)			
Log Pow	> 3			
Log Kow	> 6,5			
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.			
12.4. Mobility in soil				
Eurol Ultrance PSA 0W-30				
Ecology - soil	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the water.			
1-Decene, homopolymer, hydrogenated (680	37-01-4)			
Ecology - soil	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the water.			
12.5. Results of PBT and vPvB assessmen	ıt erine			
No additional information available				
12.6. Other adverse effects				
No additional information available				
SECTION 13: Disposal consideration	s			
13.1. Waste treatment methods				
Regional legislation (waste)	: Disposal must be done according to official regulations.			
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not discharge into drains or the environment.			
Additional information	: Hazardous waste.			
Ecology - waste materials	: Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at hazardous or special wests collection point.			

hazardous or special waste collection point.

European List of Waste (LoW) code : 13 02 06* - Synthetic engine, gear and lubricating oils

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID	
14.1. UN number					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.2. UN proper shipping name					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.3. Transport hazard class(es)					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.4. Packing group					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.5. Environmental hazards					
Dangerous for the	Dangerous for the	Dangerous for the	Dangerous for the	Dangerous for the	
environment : No	environment : No	environment : No	environment : No	environment : No	
	Marine pollutant : No				
No supplementary information available					

14.6. Special precautions for user

- Overland transport

no data available

- Transport by sea

no data available

26-2-2018 EN (English) 7/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

- Air transport

no data available

- Inland waterway transport

no data available

- Rail transport

no data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 0 %

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out

1-Decene, homopolymer, hydrogenated

SECTION 16: Other information

Full text of H- and EUH-statements:

Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
H304	May be fatal if swallowed and enters airways.
H413	May cause long lasting harmful effects to aquatic life.
EUH210	Safety data sheet available on request.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

26-2-2018 EN (English) 8/8