

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Date of issue: 13-2-2014 Revision date: 3-7-2018 Supersedes: 8-6-2015 Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

: Eurol Sportbike 10W-50 Product name

: E100184 Product code Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

: industrial use, professional use, consumer use Main use category

Use of the substance/mixture : Lubricant

Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Eurol by. Energiestraat 12 P.O. Box P.O. Box 135

7442 DA Nijverdal - The Netherlands

T +31 548 615165

reach@eurol.com - www.eurol.com

1.4. Emergency telephone number

: +31 79 3467 808 Emergency number

EVOFENEDEX

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements (CLP) : P102 - Keep out of reach of children.

EUH-statements : EUH210 - Safety data sheet available on request.

Child-resistant fastening : Not applicable Tactile warning : Not applicable

2.3. Other hazards

Other hazards not contributing to the classification

: This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classified as T/R45: May cause cancer" (Note L).". USED ENGINE OILS: Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier		Classification according to Regulation (EC) No. 1272/2008 [CLP]
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based	(CAS-No.) 72623-87-1 (EC-No.) 276-738-4 (REACH-no) 01-2119474889-13	>= 50	Asp. Tox. 1, H304

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Highly refined mineral oil (C15 -C50) substance with a Community workplace exposure limit	(REACH-no) 01-2119471299-27, 01- 2119484627-25, 01-2119487077-29	10 - 25	Not classified
Distillates (petroleum), hydrotreated heavy paraffinic	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	5 - 10	Asp. Tox. 1, H304
Polyolefine polyaminesuccinimide, polyol	(CAS-No.) 147880-09-9 (EC-No.) 604-611-9	1 - 3	Aquatic Chronic 4, H413
Bis(nonylfenyl)amine	(CAS-No.) 36878-20-3 (EC-No.) 253-249-4 (REACH-no) 01-2119488911-28	1 - 3	Aquatic Chronic 4, H413

Full text of H-statements: see section 16

SECTION 4: First aid measures

First-aid measures after eye contact

-							
л	- 4	m	loccrint	ION O	t tire	210	l measures
-	-	_	Jestin	IIOII O	1 1113	ı aıv	ı ilicasulcs

First-aid measures general

: Seek medical attention if ill effect develops.

First-aid measures after inhalation : Take victim to fresh air, in a quiet place, in an half laying position and if necessary take

medical advice. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water,

followed by warm water rinse. High-pressure injection under skin may cause serious

damage. Seek medical attention if ill effect or irritation develops.

: Remove contact lenses, if present and easy to do. Continue rinsing. Ensure adequate flushing of eyes by separating eyelids with the fingers. Obtain medical attention if pain,

blinking, tears or redness persist.

First-aid measures after ingestion : Consult a doctor/medical service if you feel unwell. If vomiting occurs spontaneously, keep

head below the hips to prevent aspiration. Do not induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : At normal ambient temperatures this product will be unlikely to present an inhalation

hazard because of its low volatility. May be harmful by inhalation if exposure to vapour,

mists or fumes resulting from thermal decomposition products occurs.

Symptoms/effects after skin contact : Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated

exposure may lead to dermatitis. High pressure injection of product into the skin may lead

to local necrosis if the product is not surgically removed.

: Unlikely to cause more than transient stinging or redness if accidental eye contact occurs. Symptoms/effects after eye contact

: Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though larger Symptoms/effects after ingestion

quantities may cause nausea and diarrhoea.

Symptoms/effects upon intravenous administration : Unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2), dry chemical powder, foam. Water fog.

: Do not use a heavy water stream. Use of heavy stream of water may spread fire. Unsuitable extinguishing media

5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustion generates: CO, CO2, POx, NOx, SOx, H2S. Metallic oxides.

Explosion hazard : Not expected to be a fire/explosion hazard under normal conditions of use.

5.3. Advice for firefighters

Precautionary measures fire : Do not enter fire area without proper protective equipment, including respiratory protection.

Firefighting instructions : Use water spray or fog for cooling exposed containers.

Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

Prevent fire fighting water from entering the environment. Sweep up and remove to a Other information suitable, clearly marked container for disposal in accordance with local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and

public waters.

6.1.1. For non-emergency personnel

Protective equipment : When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk

of splashing) then chemical resistant aprons and/or impervious chemical suits and boots

will be required. Use protective clothing.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Emergency procedures : Consider evacuation.

6.1.2. For emergency responders

Protective equipment : When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk

of splashing) then chemical resistant aprons and/or impervious chemical suits and boots

will be required.

Emergency procedures : No specific measures are necessary.

6.2. Environmental precautions

Dike for recovery or absorb with appropriate material. Notify authorities if product enters sewers or public waters. Prevent soil and water pollution. Prevent liquid from entering sewers, watercourses, underground or low areas. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

6.3. Methods and material for containment and cleaning up

For containment : Large quantities: Contain large spillage with sand or earth.

Methods for cleaning up : Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders,

sawdust). Take up large spills with pump or vacuum and finish with dry chemical

absorbent

Other information : Use suitable disposal containers. Sweep up and remove to a suitable, clearly marked

container for disposal in accordance with local regulations. On water, recover/skim from

surface and pour out in disposal container.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous.

Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and

promptly returned to a drum reconditioner or disposed of properly.

Precautions for safe handling : Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled.

Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or

smoke during use. Remove contaminated clothing and shoes.

Hygiene measures : Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with

waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing

before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep container tightly closed and in well ventilated place.

Storage conditions : Store in original container.

Incompatible products : Reacts vigorously with strong oxidizers and acids.

Maximum storage period : 5 year Storage temperature : \leq 40 °C

Information on mixed storage : Keep away from : oxidizing materials. strong acids.

Storage area : Store at ambient temperature.

Special rules on packaging : Keep container tightly closed and dry.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Highly refined mineral oil (C15 -C50)

EU - Occupational Exposure Limits

IOELV TWA (mg/m³) 5 mg/m³

Exposure-value for oil mist : 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours).

8.2. Exposure controls

Appropriate engineering controls:

Large quantities: Contain large spillage with sand or earth.

Personal protective equipment:

Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed.

3-7-2018 (Version: 3.0) EN (English) 3/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Materials for protective clothing:

PVC gloves. Neoprene or nitrile rubber gloves

Hand protection:

In case of repeated or prolonged contact wear gloves. The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream). The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Eye protection:

Eye protection should only be necessary where liquid could be splashed or sprayed

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use. Avoid repeated or prolonged skin contact. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Equipment should conform to EN 166.

Respiratory protection:

Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn. Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.

Personal protective equipment symbol(s):





Environmental exposure controls:

See Heading 12. See Heading 6.

Consumer exposure controls:

PVC gloves. Neoprene or nitrile rubber gloves.

Other information:

Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquidAppearance: Oily. liquid.Colour: Brown.Odour: characteristic.Odour threshold: no data availablepH: no data available

Relative evaporation rate (butylacetate=1) : < 0.1 Melting point : < 45 °C

Freezing point : no data available

Boiling point : > 280 °C

Flash point : 211 °C

Auto-ignition temperature : > 240 °C

Decomposition temperature : no data available

Flammability (solid, gas) : no data available

Vapour Pressure 20°C : < 0,1 hPa

Relative vapour density at 20 °C : > 1 (air=1)

Relative density : no data available

Density : 0,845 - 0,855 kg/l

Solubility : insoluble in water.

Log Pow : > 3

Viscosity, kinematic : 100 - 150 mm²/s
Viscosity, dynamic : no data available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Explosive properties : no data available
Oxidising properties : no data available
Explosive limits : 0,6 - 7 vol %

9.2. Other information

VOC content : 0 %

Other properties : Gas/vapour heavier than air at 20'C.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

Moisture. Overheating.

10.5. Incompatible materials

Strong oxidizing agents. strong acids.

10.6. Hazardous decomposition products

CO, CO2, POx, NOx, SOx, H2S. Metallic oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
LD50 oral rat > 5000 mg/kg		
LD50 dermal rat	> 5000 mg/kg	
LC50 inhalation rat (mg/l) > 5,53 mg/l		

Bis(nonylfenyl)amine (36878-20-3)	
LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rat	> 2000 ml/kg (OECD 402 method)

Skin corrosion/irritation : Not classified Serious eye damage/irritation : Not classified Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified STOT-single exposure : Not classified STOT-repeated exposure : Not classified Aspiration hazard : Not classified

Furo	l Sno	rthike	10W	/-5 0

Viscosity, kinematic 100 - 150 mm²/s

: Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products. Likely route of exposure: ingestion, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Other information

Ecology - general : Ecotoxicological data have not been determined specifically for this product. Information

given is based on a knowledge of the components and the ecotoxicology of similar

products.

Ecology - water : This product floats on water and may affect the oxygen-balance in the water.

Hazardous to the aquatic environment, short-term

(acute)

: Not classified

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

 $\label{thm:long-term} \mbox{Hazardous to the aquatic environment, long-term}$

(chronic)

: Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
LC50 fish 1	100 mg/l	
EC50 Daphnia 1	10000 mg/l	

Bis(nonylfenyl)amine (36878-20-3)				
LC50 fish 1	> 100 mg/l 96h; Brachydanio rerio (zebra-fish)			
EC50 Daphnia 1	> 100 mg/l EC50 48h - Daphnia magna [mg/l]			
EC50 72h algae (1)	600 mg/l			
ErC50 (algae)	> 100 mg/l 72h; Desmodesmus subspicauts			
12.2. Persistence and degradability	12.2. Persistence and degradability			
Eurol Sportbike 10W-50				
Persistence and degradability	Not readily biodegradable.			

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Biodegradation	31 %

Bis(nonylfenyl)amine (36878-20-3)		
Biodegradation 0 % Sturm - 28 days		
2.3. Bioaccumulative potential		
Eurol Sportbike 10W-50		
Log Pow	> 3	
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.	

Bis(nonylfenyl)amine (36878-20-3)				
Bioconcentration factor (BCF REACH)	1584,89			
12.4. Mobility in soil	2.4. Mobility in soil			
Eurol Sportbike 10W-50				
	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the water.			

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not discharge

into drains or the environment.

Additional information : Hazardous waste.

Ecology - waste materials : Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden. Empty containers retain product residue (solid, liquid, and/or vapor) and can be

dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at hazardous or special waste collection point.

European List of Waste (LoW) code : 13 02 06* - Synthetic engine, gear and lubricating oils

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

3-7-2018 (Version: 3.0) EN (English) 6/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID			
14.1. UN number	4.1. UN number						
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable			
14.2. UN proper shippin	g name						
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable			
14.3. Transport hazard	class(es)						
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable			
14.4. Packing group							
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable			
14.5. Environmental haz	14.5. Environmental hazards						
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No			
No supplementary information	No supplementary information available						

14.6. Special precautions for user

Overland transport

no data available

Transport by sea

no data available

Air transport

no data available

Inland waterway transport

no data available

Rail transport

no data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 0 %

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:	
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
H304	May be fatal if swallowed and enters airways.
H413	May cause long lasting harmful effects to aquatic life.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EUH210	Safety data sheet available on request.

SDS EU (REACH Annex II) - Copy Eurol

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.