



Eurol ATF III G

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 12-2-2014 Revision date: 28-11-2019 Supersedes: 16-4-2019 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Eurol ATF III G
Product code : E113665
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : industrial use, professional use, consumer use
Use of the substance/mixture : Lubricant
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Eurol bv.
Energiestraat 12
P.O. Box P.O. Box 135
7442 DA Nijverdal - The Netherlands
T +31 548 615165
reach@eurol.com - www.eurol.com

1.4. Emergency telephone number

Emergency number : +31 79 3467 808
EVOFENEDEX

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements (CLP) : P102 - Keep out of reach of children.
EUH-statements : EUH210 - Safety data sheet available on request.
Child-resistant fastening : Not applicable
Tactile warning : Not applicable

2.3. Other hazards

Other hazards not contributing to the classification : This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classified as T/R45: May cause cancer" (Note L)."

EuroI ATF III G

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|-------|-----------------------------------------------------------------|
| Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] | (CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25 | ≥ 50 | Asp. Tox. 1, H304 |
| Methacrylate copolymer | (CAS-No.) confidential | 1 – 3 | Eye Irrit. 2, H319 |
| Distillates (petroleum), hydrotreated light paraffinic | (CAS-No.) 64742-55-8 (EC-No.) 265-158-7 (EC Index-No.) 649-468-00-3 (REACH-no) 01-2119487077-29 | 1 – 3 | Asp. Tox. 1, H304 |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | (CAS-No.) 64742-65-0 (EC-No.) 265-169-7 (REACH-no) 01-2119471299-27 | 1 – 3 | Asp. Tox. 1, H304 |

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| First-aid measures general | : Seek medical attention if ill effect develops. |
| First-aid measures after inhalation | : Take victim to fresh air, in a quiet place, in an half laying position and if necessary take medical advice. Allow the victim to rest. |
| First-aid measures after skin contact | : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. High-pressure injection under skin may cause serious damage. Seek medical attention if ill effect or irritation develops. |
| First-aid measures after eye contact | : Remove contact lenses, if present and easy to do. Continue rinsing. Ensure adequate flushing of eyes by separating eyelids with the fingers. Obtain medical attention if pain, blinking, tears or redness persist. |
| First-aid measures after ingestion | : Consult a doctor/medical service if you feel unwell. If vomiting occurs spontaneously, keep head below the hips to prevent aspiration. Do not induce vomiting. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|--------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Symptoms/effects after inhalation | : At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs. |
| Symptoms/effects after skin contact | : Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed. |
| Symptoms/effects after eye contact | : Unlikely to cause more than transient stinging or redness if accidental eye contact occurs. |
| Symptoms/effects after ingestion | : Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea. |
| Symptoms/effects upon intravenous administration | : Unknown. |

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

EuroI ATF III G

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : carbon dioxide (CO₂), dry chemical powder, foam. Water fog.
Unsuitable extinguishing media : Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Combustion generates: CO, CO₂, POx, NOx, SOx, H₂S.
Explosion hazard : Not expected to be a fire/explosion hazard under normal conditions of use.

5.3. Advice for firefighters

- Precautionary measures fire : Do not enter fire area without proper protective equipment, including respiratory protection.
Firefighting instructions : Use water spray or fog for cooling exposed containers.
Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.
Other information : Prevent fire fighting water from entering the environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and public waters.

6.1.1. For non-emergency personnel

- Protective equipment : When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Use protective clothing.
Emergency procedures : Consider evacuation.

6.1.2. For emergency responders

- Protective equipment : When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
Emergency procedures : No specific measures are necessary.

6.2. Environmental precautions

Dike for recovery or absorb with appropriate material. Notify authorities if product enters sewers or public waters. Prevent soil and water pollution. Prevent liquid from entering sewers, watercourses, underground or low areas. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

6.3. Methods and material for containment and cleaning up

- For containment : Large quantities: Contain large spillage with sand or earth.
Methods for cleaning up : Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Take up large spills with pump or vacuum and finish with dry chemical absorbent.
Other information : Use suitable disposal containers. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations. On water, recover/skim from surface and pour out in disposal container.

6.4. Reference to other sections

For further information refer to section 13.

Eurol ATF III G

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Additional hazards when processed | : Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. |
| Precautions for safe handling | : Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes. |
| Hygiene measures | : Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse. |

7.2. Conditions for safe storage, including any incompatibilities

| | |
|------------------------------|---------------------------------------------------------------|
| Technical measures | : Keep container tightly closed and in well ventilated place. |
| Storage conditions | : Keep only in original container. |
| Incompatible products | : Reacts vigorously with strong oxidizers and acids. |
| Maximum storage period | : 5 year |
| Storage temperature | : ≤ 40 °C |
| Information on mixed storage | : Keep away from : oxidizing materials. Strong acids. |
| Storage area | : Store at ambient temperature. |
| Special rules on packaging | : Keep container tightly closed and dry. |

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure-value for oil mist : 10 mg/m³ (15 min.) or 5 mg/m³ (8 hours).

8.2. Exposure controls

Appropriate engineering controls:

Large quantities: Contain large spillage with sand or earth.

Personal protective equipment:

Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed.

Materials for protective clothing:

PVC gloves. Neoprene or nitrile rubber gloves

Hand protection:

In case of repeated or prolonged contact wear gloves. The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream). The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Eye protection:

Eye protection should only be necessary where liquid could be splashed or sprayed

EuroI ATF III G

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use. Avoid repeated or prolonged skin contact. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Equipment should conform to EN 166.

Respiratory protection:

Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn. Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.

Personal protective equipment symbol(s):



Environmental exposure controls:

See Heading 12. See Heading 6.

Consumer exposure controls:

PVC gloves. Neoprene or nitrile rubber gloves.

Other information:

Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--------------------------------------------|-------------------------------|
| Physical state | : liquid |
| Appearance | : Oily, liquid. |
| Colour | : Red. |
| Odour | : characteristic. |
| Odour threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butylacetate=1) | : < 0,1 |
| Melting point | : ≤ -48 °C |
| Freezing point | : No data available |
| Boiling point | : > 280 °C |
| Flash point | : > 186 °C |
| Auto-ignition temperature | : > 240 °C |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapour Pressure 20°C | : < 0,1 hPa |
| Relative vapour density at 20 °C | : > 1 (air=1) |
| Relative density | : No data available |
| Density | : 0,855 – 0,865 kg/l |
| Solubility | : insoluble in water. |
| Log Pow | : > 3 |
| Viscosity, kinematic | : 75 – 150 mm ² /s |
| Viscosity, dynamic | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |
| Explosive limits | : 0,6 – 7 vol % |

9.2. Other information

| | |
|------------------|----------------------------------------|
| VOC content | : 0 % |
| Other properties | : Gas/vapour heavier than air at 20°C. |

EuroI ATF III G

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

Moisture. Overheating.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

| | |
|-----------------------|--------------|
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rat | > 5000 mg/kg |
| LC50 Inhalation - Rat | > 5,53 mg/l |

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

EuroI ATF III G

| | |
|----------------------|-----------------------------|
| Viscosity, kinematic | 75 – 150 mm ² /s |
|----------------------|-----------------------------|

Other information : Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products. Likely route of exposure: ingestion, skin and eye.

EuroI ATF III G

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 12: Ecological information

12.1. Toxicity

| | |
|-----------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ecology - general | : Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. |
| Ecology - water | : This product floats on water and may affect the oxygen-balance in the water. |
| Hazardous to the aquatic environment, short-term (acute) | : Not classified |
| Hazardous to the aquatic environment, long-term (chronic) | : Not classified |

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

| | |
|----------------|------------|
| LC50 fish 1 | 100 mg/l |
| EC50 Daphnia 1 | 10000 mg/l |

12.2. Persistence and degradability

| | |
|-------------------------------|----------------------------|
| EuroI ATF III G | |
| Persistence and degradability | Not readily biodegradable. |

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

| | |
|----------------|------|
| Biodegradation | 31 % |
|----------------|------|

12.3. Bioaccumulative potential

| | |
|---------------------------|---------------------------------------------------------------------------------------|
| EuroI ATF III G | |
| Log Pow | > 3 |
| Bioaccumulative potential | This product is not expected to bioaccumulate through food chains in the environment. |

12.4. Mobility in soil

| | |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EuroI ATF III G | |
| Ecology - soil | Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the water. |

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Regional legislation (waste) | : Disposal must be done according to official regulations. |
| Waste disposal recommendations | : Dispose in a safe manner in accordance with local/national regulations. Do not discharge into drains or the environment. |

EuroI ATF III G

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| | |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Additional information | : Hazardous waste. |
| Ecology - waste materials | : Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at hazardous or special waste collection point. |
| European List of Waste (LoW) code | : 13 02 06* - Synthetic engine, gear and lubricating oils |

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

| ADR | IMDG | IATA | ADN | RID |
|-----------------------------------------|-------------------------------------------------------------|------------------------------------|------------------------------------|------------------------------------|
| 14.1. UN number | | | | |
| Not applicable | Not applicable | Not applicable | Not applicable | Not applicable |
| 14.2. UN proper shipping name | | | | |
| Not applicable | Not applicable | Not applicable | Not applicable | Not applicable |
| 14.3. Transport hazard class(es) | | | | |
| Not applicable | Not applicable | Not applicable | Not applicable | Not applicable |
| 14.4. Packing group | | | | |
| Not applicable | Not applicable | Not applicable | Not applicable | Not applicable |
| 14.5. Environmental hazards | | | | |
| Dangerous for the environment : No | Dangerous for the environment : No Marine pollutant : No | Dangerous for the environment : No | Dangerous for the environment : No | Dangerous for the environment : No |
| No supplementary information available | | | | |

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

No data available

Air transport

No data available

Inland waterway transport

No data available

Rail transport

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

EuroI ATF III G

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 0 %

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

| Full text of H- and EUH-statements: | |
|-------------------------------------|-----------------------------------------------|
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Eye Irrit. 2 | Serious eye damage/eye irritation, Category 2 |
| H304 | May be fatal if swallowed and enters airways. |
| H319 | Causes serious eye irritation. |
| EUH210 | Safety data sheet available on request. |

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.