



Quality is in our nature

Passenger car engine oils - Fully Synthetic

Eurol Ultrance PSA 0W-30

Fully synthetic mid SAPS motor oil for gasoline and diesel engines

Description

Eurol Ultrance PSA 0W-30 is a fully synthetic ultra high performance oil for gasoline and diesel engines in passenger cars, especially for the most recent Peugeot and Citroën engines.

vehicles for which an engine oil meeting ACEA C2 (2012) with the viscosity grade 0W-30 is prescribed.

Eurol Ultrance PSA 0W-30 quickly provides an extremely stable lubricant film at the cold start and offers high thermal stability under heavy duty operating conditions.

Eurol Ultrance PSA 0W-30 offers optimum dispersancy and detergency, keeping the engine clean.

Eurol Ultrance PSA 0W-30 provides maximum protection against rust and corrosion, while special additives keep all parts free from dirt, sludge and deposits.

Eurol Ultrance PSA 0W-30 offers extra fuel saving properties and allows long drain intervals (up to 30.000 km) for the latest models of Peugeot and Citroën.

Eurol Ultrance PSA 0W-30 is also recommended for

Specifications

Performance level

ACEA C2

PSA B71 2312

Recommended for use

Fiat 9.55535-GS1

Fiat 9.55535-DS1

Physical properties

| | | |
|-------------------------------|--------------|-------------|
| Colour | Brown | |
| Density at 20°C | 0.84 kg/l | ASTM D 1298 |
| Viscosity, kinematic at 40°C | 53.1 cSt | ASTM D 445 |
| Viscosity, kinematic at 100°C | 9.7 cSt | ASTM D 445 |
| Viscosity Index | 169 | ASTM D 2270 |
| Viscosity, dynamic (CCS) | 5569 cP | ASTM D 2602 |
| Base number | 6.2 mg KOH/g | ASTM D 2896 |
| Sulphated ash | 0.58 wt% | ASTM D 874 |
| Flash point | 200 °C | ASTM D 93 |
| Pour point | -45 °C | ASTM D 97 |

E100018

Version 1.0, 24-04-2018

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com