



Quality is in our nature

Passenger car engine oils - Fully Synthetic

Eurol Ultrance FDE 0W-30

Fully synthetic mid-SAPS motor oil for gasoline and diesel engines

Description

Eurol Ultrance FDE 0W-30 is a fully synthetic ultra high performance oil for gasoline and diesel engines in passenger cars, especially for the most recent Ford diesel engines. Eurol Ultrance FDE 0W-30 fulfills the requirements of Ford WSS-M2C950-A.

Eurol Ultrance FDE 0W-30 quickly provides an extremely stable lubricant film at the cold start and offers high thermal stability under heavy duty operating conditions.

Eurol Ultrance FDE 0W-30 offers optimum dispersancy and detergency, keeping the engine clean.

Eurol Ultrance FDE 0W-30 provides maximum protection against rust and corrosion, while special additives keep all parts free from dirt, sludge and deposits.

Eurol Ultrance FDE 0W-30 is also recommended for vehicles for which an engine oil meeting ACEA C2 (2012) with the viscosity grade 0W-30 is prescribed.

Specifications

Performance level

ACEA C2

Ford WSS M2C-950A

Recommended for use

STJLR 03.5007

Physical properties

Colour	Brown	
Density at 20°C	0.839 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	47.7 cSt	ASTM D 445
Viscosity, kinematic at 100°C	9.8 cSt	ASTM D 445
Viscosity Index	197	ASTM D 2270
Viscosity, dynamic (CCS)	5313 cP	ASTM D 2602
Base number	8.0 mg KOH/g	ASTM D 2896
Flash point	200 °C	ASTM D 93
Pour point	-51 °C	ASTM D 97

E100025

Version 1.0, 30-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com