





### Passenger car engine oils - Fully Synthetic

# **Eurol Actence 5W-30**

## Fully synthetic long-life motor oil ACEA C4

### **Description**

Eurol Actence 5W-30 is a fully synthetic motor oil for gasoline and diesel engines in passenger cars and light duty commercial vehicles. This oil can be applied for cars equipped with catalytic converters, turbo charged engines and for direct fuel injection systems.

Eurol Actence 5W-30 offers an extremely high protection over prolonged drain intervals. Especially recommended for Euro-4 cars for which ACEA C4 is prescribed, to prevent soot filters from blocking.

Because of this, Eurol Actence 5W-30 has low sulphated ash contents and also low levels of phosphor and sulphur (so called "low-SAPS" technology).

Eurol Actence 5W-30 not only offers an extremely good wear protection but also protects against rust and oxidation, while special additives keep the engine clean from dirt, sludge and deposits during the sometimes extremely long drain intervals.

**Specifications** 

Approved
Renault RN0720
Performance level
ACEA C4
MB 229.51
MB 226.51

Eurol Actence 5W-30 provides an extremely quick and stable lubricant film at the cold start and a high thermal stability under heavy duty operating conditions.

#### **Physical properties**

| Colour                        | Brown        |             |
|-------------------------------|--------------|-------------|
| Density at 20°C               | 0.847 kg/l   | ASTM D 1298 |
| Viscosity, kinematic at 40°C  | 69.7 cSt     | ASTM D 445  |
| Viscosity, kinematic at 100°C | 12.1 cSt     | ASTM D 445  |
| Viscosity Index               | 172          | ASTM D 2270 |
| Viscosity, dynamic (CCS)      | 5190 cP      | ASTM D 2602 |
| Base number                   | 7.8 mg KOH/g | ASTM D 2896 |
| Sulphated ash                 | 0.51 wt%     | ASTM D 874  |
| Flash point                   | 210 °C       | ASTM D 93   |
| Pour point                    | -42 °C       | ASTM D 97   |

E100058 Version 3.0, 18-12-2018