



Quality is in our nature

Passenger car engine oils - Fully Synthetic

## Eurol Super Lite 5W-30

Fully synthetic oil for gasoline and diesel engines, with or without turbo

### Description

Eurol Super Lite 5W-30 is a fully synthetic motor oil for gasoline and diesel engines in passenger cars and light duty commercial vehicles. This oil can be applied for cars equipped with catalytic converters, turbo charged engines and for direct fuel injection systems.

Eurol Super Lite 5W-30 provides an extremely quick and stable lubricant film at the cold start and offers high thermal stability under heavy duty operating conditions.

Eurol Super Lite 5W-30 not only offers extremely good wear protection, but also protects against rust and corrosion, while special additives keep all parts free from dirt, sludge and deposits.

Eurol Super Lite 5W-30 offers fuel saving properties and can be mixed with both synthetic and mineral motor oils.

### Specifications

Approval pending

ACEA A5/B5

Performance level

API SN/CF

Recommended for use

ACEA A3/B4

VW 502.00

MB 229.3

Renault RN0710

Renault RN0700

VW 505.00

### Physical properties

Colour	Brown	
Density at 20°C	0.854 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	65.3 cSt	ASTM D 445
Viscosity, kinematic at 100°C	11.4 cSt	ASTM D 445
Viscosity Index	170	ASTM D 2270
Viscosity, dynamic (CCS)	5260 cP	ASTM D 2602
Base number	10.4 mg KOH/g	ASTM D 2896
Sulphated ash	1.16 wt%	ASTM D 874
Flash point	200 °C	ASTM D 93
Pour point	-33 °C	ASTM D 97

E100091

Version 1.0, 03-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com