





Motorcycle oils 4T - Mineral

# **Eurol 4T Road 10W-40**

## Mineral motor oil for 4-stroke motorcycles

#### **Description**

Eurol 4T Road 10W-40 is a mineral engine oil without friction modifiers and has been especially developed for 4-stroke motorcycles.

This oil can also be used in motorcycle transmissions where an API SG oil is prescribed.

Eurol 4T Road 10W-40 is suitable for touring, racing, as well as for cross applications, under all conditions.

Eurol 4T Road 10W-40 offers an excellent protection against wear, deposits, sludge and oxidation. Even under the most severe operating conditions air-absorption and foam building are minimised.

Eurol 4T Road 10W-40 has a very low volatility by which oil thickening and oil consumption are reduced to a minimum. Due to the special formulation, this oil offers excellent protection to gearboxes and wet disc clutches.

Even under the extreme conditions in gearboxes, the selected oil thickener will hardly break down so that at

### **Specifications**

Performance level API SJ JASO MA JASO MA2 high temperatures the viscosity stays in grade to guarantee a solid lubricant film.

#### **Physical properties**

Colour	Brown	
Density at 20°C	0.858 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	95.4 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.5 cSt	ASTM D 445
Viscosity Index	158	ASTM D 2270
Viscosity, dynamic (CCS)	6130 cP	ASTM D 2602
Flash point	212 °C	ASTM D 93
Pour point	-42 °C	ASTM D 97

E100098 Version 1.0, 04-06-2018