

Quality is in our nature



Passenger car engine oils - Semi-synthetic

Eurol TurboCat 10W-40

Universal semi-synthetic Motor oil

Description

Eurol Turbocat 10W-40 is a semi-synthetic engine oil recommended for petrol and diesel engines. Because of the high viscosity index, the oil assures an excellent cold start as well as an excellent lubricating film with high temperatures.

Eurol Turbocat 10W-40 takes care of trouble free functioning of the engine, because of the chosen additive package. The oil helps reducing the fuel consumption as well as reducing emission levels. Because of the unique formulation a low evaporation under severe operating conditions is guaranteed.

In addition, Eurol Turbocat 10W-40 gives optimum protection against wear and has strong anti -corrosion and anti-foam characteristics as well as a high resistance against oxidation. Together with the excellent detergent/dispersant properties, this oil ensures a clean and reliable engine.

Specifications

Performance level
API SL/CF
ACEA A3/B3
Recommended for use
MB 229.1
VW 501.01
VW 505.00

Physical properties

Colour	Brown	
Density at 20°C	0.861 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	100.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	15 cSt	ASTM D 445
Viscosity Index	156	ASTM D 2270
Viscosity, dynamic (CCS)	5540 cP	ASTM D 2602
Base number	8.0 mg KOH/g	ASTM D 2896
Sulphated ash	0.95 wt%	ASTM D 874
Flash point	206 °C	ASTM D 93
Pour point	-39 ℃	ASTM D 97

E100114 Version 3.0, 19-12-2018