



Quality is in our nature

Nautic line

Eurol Nautic L. 15W-40 SHX

Mineral motor oil for advanced diesel motors without particle filter

Description

Eurol Nautic Line 15W-40 SHX is a robust motor oil, developed according to the latest oil usage and emission requirements, and fulfils all current quality requirements for European as well as American and Japanese diesel oils.

circumstances, allowing Eurol Nautic Line 15W-40 SHX to easily cover the prescribed oil change term, regardless of the type of motor.

Eurol Nautic Line 15W-40 SHX is pre-eminently suited for heavy diesel engines, but can also be used in petrol, LPG and light diesel motors, whether or not they are equipped with a turbo and/or catalytic converter and/or common rail.

Eurol Nautic Line 15W-40 SHX amply fulfils the lowered limits on sedimentation on the piston crown, in the top compression ring groove and the rest of the piston.

Due to its stability against high temperatures and ageing, as well as the highly cleansing additives, Eurol Nautic Line SHX ensures that both the motor and the oil remain in good condition.

Wear is limited to a minimum, even under the harshest

Specifications

Performance level	CES 20077
API CI-4/SL	Deutz DQC III-10
ACEA E7	Global DHD-1
MB 228.3	MTU type 2
MB 228.1	
MAN M 3275	
Volvo VDS-3	
Volvo VDS-2	
Caterpillar ECF-2	
Caterpillar ECF-1-A	
CES 20076	

Physical properties

Colour	Brown	
Density at 20°C	0.884 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	108.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.5 cSt	ASTM D 445
Viscosity Index	136	ASTM D 2270
Viscosity, dynamic (CCS)	6098 cP	ASTM D 2602
Base number	11.5 mg KOH/g	ASTM D 2896
Sulphated ash	1.5 wt%	ASTM D 874
Flash point	210 °C	ASTM D 93
Pour point	-39 °C	ASTM D 97

E100143

Version 2.0, 18-04-2018

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com