



Quality is in our nature

Nautic line - Mineral

Eurol Nautic L.10W-40 FCW

4 stroke oil for outboard motors

Description

Eurol Nautic Line 10W-40 FCW is a motor oil that ensures an optimal lubrication and protection of 4 stroke outboard motors.

always best to ensure timely oil changes.

Eurol Nautic Line 10W-40 FCW fulfils the NMMA FCW requirements, such as protection against rust and corrosion through contact with (salt) water, a limited decrease in viscosity after long-term use and an excellent protection against wear and sedimentation, especially in case of fuel dilution*.

*Fuel dilution can happen in outboard motors, when the motor runs for an extended time in neutral, and unburnt fuel leaks into the crankcase.

Eurol Nautic Line 10W-40 FCW contains special additives that limit wear to a minimum both at low and high speeds.

Thanks to special additives, Eurol Nautic Line 10W-40 FCW will keep providing its high performance level even after the oil change term has passed. However, it is

Specifications

Performance level

API SL

JASO MA

NMMA FC-W

Physical properties

Colour	Brown	
Density at 20°C	0.866 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	101 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.8 cSt	ASTM D 445
Viscosity Index	153	ASTM D 2270
Viscosity, dynamic (CCS)	5600 cP	ASTM D 2602
Sulphated ash	0.89 wt%	ASTM D 874
Flash point	201 °C	ASTM D 93
Pour point	-33 °C	ASTM D 97

E100144

Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com