



Quality is in our nature

Transmission oils - Mineral

Eurol HPG 75W-80 GL5 CP

Mineral transmission oil for Citroën, Peugeot, Renault and Volvo

Description

Eurol HPG 75W-80 GL5 CP is a thin mineral transmission oil, especially developed for manually shifted gearboxes of Citroën, Peugeot, Renault and Volvo.

Eurol HPG 75W-80 GL5 CP provides excellent stability, very good anti-wear properties and a low foam tendency. The high viscosity index guarantees optimum lubrication under all operating conditions.

Eurol HPG 75W-80 GL5 CP is inhibited with special anti-corrosion, anti wear and anti-oxidation additives. The excellent low temperature fluidity improves shifting at low temperatures and contributes to a lower fuel consumption.

Specifications

Performance level

API GL-5
MIL-L-2105D
ZF TE-ML
05A/07A/08A/12E/16B/16C
/16D/17B/19B/21A
MAN 342 Type M2

Recommended for use

PSA Peugeot Citroën B71
2330

Physical properties

Colour	Yellow	
Density at 20°C	0.87 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	55.3 cSt	ASTM D 445
Viscosity, kinematic at 100°C	10.6 cSt	ASTM D 445
Viscosity Index	185	ASTM D 2270
Flash point	172 °C	ASTM D 93
Pour point	-48 °C	ASTM D 97

E110072

Version 1.0, 04-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com