



Quality is in our nature

Transmission oils - Semi-synthetic

# Eurol MTF 75W GL4

Synthetic gear oil with fuel-saving properties

## Description

Eurol MTF 75W GL4 is a synthetic gear oil, which can be used in final drives and manual transmissions.

Eurol MTF 75W GL4 is very well compatible with synchromesh and ensures very smooth shifting even at low temperatures.

Eurol MTF 75W GL4 contains special friction modifiers, which ensure sustainable fuel saving and less heat development.

Eurol MTF 75W GL4 ensures adequate lubrication at both very low, as very high temperatures and protects against corrosion, wear, thickening and deposits.

Eurol MTF 75W GL4 is compatible with most elastomers and seal materials and does not foam under extreme loads.

## Specifications

### Performance level

API GL-4

MIL-L-2105

### Recommended for use

VW TL 726 (G 052 726 A2/G

055 726 A2/G 060 726

A2/G 070 726 A2)

VW G 052 512 (A2)

VW G 052 178 A2

VW G 052 171 A1/A2

## Physical properties

Colour	Light yellow	
Density at 20°C	0.877 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	40.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	6.7 cSt	ASTM D 445
Flash point	221 °C	ASTM D 93
Pour point	-44 °C	ASTM D 97

E110073

Version 1.0, 04-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com