



Quality is in our nature

Automatic transmission fluids - Fully Synthetic

Eurol ATF 6700

Synthetic all-round low viscosity Automatic Transmission oil

Description

Eurol ATF 6700 is a synthetic automatic transmission oil, which has been especially developed for automatic gear boxes requiring low viscosity ATF.

Eurol ATF 6700 ensures easy shifting under all operating temperatures, without unnecessary friction. Because of the low pour point and the high VI, Eurol ATF 6700 can be applied in a wide temperature range.

Because of the excellent oxidation and thermal stability, Eurol ATF 6700 keeps its unique properties, so it easily meets the prescribed drain intervals.

A unique combination of synthetic base oils and state-of-the-art additives, guarantee all-round, easy shifting. The low viscosity ensures a fuel economy benefit compared to conventional viscosity ATF's.

Specifications

<u>Recommended for use</u>	HYUNDAI NWS-9638	MB 236.41	ZF Lifeguardfluid8
Aisin Warner AW-1	Hyundai SP IV, SPH-IV	Mercon LV	
Bentley Oil PY112995PA	JAGUAR 02JDE26444	Mercon SP	
CHRYSLER 68157995AA	Jaguar Fluid 8432	Mitsubishi SP-IV & ATF J-2	
DSI H 6-SPEED	JWS 3324 (ATF WS)	Nissan Matic S	
TRANSMISSION (AT 3292)	LAND ROVER LR023288	SAAB 93 165 147	
Fiat 9.55550-AV2	Land Rover TYK 500050	Toyota Type WS (JWS 3324)	
Fiat 9.55550-AV5	M-1375.4	VW G 055 005	
Ford WSS-M2C924-A	Maserati 231603	VW G 055 162	
GM Dexron VI	Mazda FZ	VW G 055 540	
Honda ATF DW-1	MB 236.12	VW G 060 162	

Physical properties

Colour	Amber	
Density at 20°C	0.843 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	29.4 cSt	ASTM D 445
Viscosity, kinematic at 100°C	6 cSt	ASTM D 445
Viscosity Index	154	ASTM D 2270
Flash point	200 °C	ASTM D 93
Pour point	-45 °C	ASTM D 97

Available in 1L - 5L - 20L - 60L - 210L - IBC

E113653
Version 1.0, 04-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com