



Quality is in our nature

Automatic transmission fluids - Semi-synthetic

Eurol ATF III G

Synthetic automatic transmission fluid Dexron III G

Description

Eurol ATF III G is a synthetic automatic transmission fluid, especially developed for new (after 1997) and older (automatic) transmissions build by Ford and GM, as well as for many other brands. It is also suitable for power steering systems, some hydraulic systems and for rotary air compressors where an excellent low temperature fluidity is required.

characteristics of Eurol ATF III G comply to the most modern demands in a very broad temperature range.

Eurol ATF III G has a very high viscosity index and offers resistance against corrosion and foam building. It also has good anti oxidation and anti wear properties.

Eurol ATF III G has an extremely low pour point which allows easy gear shifting at cold starts. Seal are not affected by this ATF.

The Dexron III G specification differs from DEXRON III F by adding two extra tests. An 'electronically controlled converter clutch (ECCC) test' and a 'sprag wear test', by which the DEXRON III specification has been upgraded to the latest demands. This is why the friction

Specifications

Performance level

Allison C-4
Ford Mercon
GM Dexron III G
MAN Typ Z1/V1
MB 236.1
Voith 55.6335
ZF TE-ML
02F/03D/09/11B/17C
ZF TE-ML 04D/14A
Caterpillar TO-2

Recommended for use

MAN 339 Type V2
MAN 339 Z-2
Volvo 97341

Physical properties

Colour	Red	
Density at 20°C	0.859 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	37.3 cSt	ASTM D 445
Viscosity, kinematic at 100°C	7.4 cSt	ASTM D 445
Viscosity Index	169	ASTM D 2270
Flash point	186 °C	ASTM D 93
Pour point	-48 °C	ASTM D 97

E113665

Version 1.1, 18-09-2020

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com