



Quality is in our nature

Scooter oils 2T - Mineral

Eurol Nautic L. Sup Outb. 2T

Mineral 2-stroke oil for lubrication of modern outboard motors

Description

Eurol Nautic Line Super Outboard 2T is a self-mixing 2-stroke oil, especially developed for the lubrication of modern outboard motors and is suitable for both pre-mix systems, as well for oil injection systems.

Eurol Nautic Line Super Outboard 2T is formulated with carefully selected base oils and special additives, providing a long-lasting protection. Due to a very strong lubricating film, a perfect lubrication is guaranteed, even at high temperatures.

Eurol Nautic Line Super Outboard 2T effectively protects the vital engine parts from wear and corrosion and prevents from deposits on pistons and in the exhaust system. With this oil CO₂ emission is strongly reduced.

"Mixing ratio:

Maximum 1:100, according to manufacturers instructions"

Specifications

Performance level

NMMA TC-W3

Physical properties

Colour	Blue	
Density at 20°C	0.869 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	42.3 cSt	ASTM D 445
Viscosity, kinematic at 100°C	6.8 cSt	ASTM D 445
Viscosity Index	116	ASTM D 2270
Base number	8.0 mg KOH/g	ASTM D 2896
Flash point	134 °C	ASTM D 93
Pour point	-33 °C	ASTM D 97

E128430

Version 1.1, 24-08-2020

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com