



Quality is in our nature

Coolants & screenwash

Eurol Antifreeze GLX

Silicate-free, long-life anti-freeze TL-VW 774 F (G12+)

Description

Eurol Antifreeze GLX is a new generation anti-freeze, based on mono-ethylene-glycol, in which a patented silicate-free technology on carboxyl-acid base is being used. This technology is known under the name OAT (Organic Acid Technology).

Eurol Antifreeze GLX prevents from scale and offers excellent protection against cavitation. Moreover, it protects against corrosion of metal parts in the cooling system and particularly aluminum and steel-alloys.

Eurol Antifreeze GLX does not contain nitrite, amines, borate, phosphate, nitrate or silicate and in this way, contributes to a cleaner environment.

Eurol Antifreeze GLX is completely safe for rubber, plastics, metals and aluminum parts or alloys.

Eurol Antifreeze GLX is a modern coolant for water-cooled combustion engines and protects the system from freezing up to -37 °C when diluted with water for 50:50

vol%. With a 40:60 vol% (antifreeze: Water) dilution a freezing protection of -26°C will be obtained. Mixtures with more than 67 vol% of Antifreeze is not recommended.

Vol% in water : 25 30 33 40 50

Frost protection (°C) : -11 -16 -18 -26 -37

Specifications

Performance level

VW TL-774 F (G12+)

VW TL-774 D (G12)

BS 6580

ASTM D4985

ASTM D4656

ASTM D3306

Renault Type D

NATO S-759

JASO M325

Physical properties

Colour	Pink	
Density at 20°C	1.117 kg/l	ASTM D 1298
Flash point	111 °C	ASTM D 93

Available in 1L - 5L - 20L - 60L - 200L - 210L - IBC - BULK

E503152

Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com