



Quality is in our nature

Coolants & screenwash - Cooling fluids

# Eurol Coolant -36°C G11

## Long-Life Coolant

### Description

Eurol Coolant -36 G11 is recommended for use in cooling systems of liquid cooled automotive and industrial internal combustion engines.

Eurol Coolant -36 G11 protects car, truck and bus engines of both ferrous and aluminium construction against corrosion and frost damage. It contains a blend of inhibitors designed to give a high degree of corrosion protection to engine components such as radiators, cylinder blocks/heads and water pumps. Eurol Coolant -36 G11 provides year-round frost and corrosion protection.

Dilution of the coolant with water is not recommended.

Free of nitrite, amine and phosphate.

### Specifications

|                          |                            |
|--------------------------|----------------------------|
| <u>Performance level</u> | BMW GS 94000 / N 600       |
| VW TL-774 C (G11)        | 69.0                       |
| BS 6580                  | <u>Recommended for use</u> |
| ASTM D3306 / D4656 /     | SAE J1034                  |
| D4985                    | NATO S-759                 |
| AFNOR NFR 15-601         | JASO M325                  |
| MB 326.2                 |                            |
| MB 326.0                 |                            |
| MAN 324 Typ NF           |                            |
| MTU MTL 5048             |                            |
| Fiat 9.55523             |                            |

### Physical properties

|                  |            |             |
|------------------|------------|-------------|
| Colour           | Green      |             |
| Density at 20°C  | 1.075 kg/l | ASTM D 1298 |
| Flash point      | 111 °C     | ASTM D 93   |
| Frost protection | -36 °C     | ASTM D 1177 |

E504010

Version 1.1, 13-02-2020

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com