



Quality is in our nature

Coolants & screenwash - Cooling fluids

Eurol Coolant -36°C BS 6580

Meets BS 6580 standard, suitable for open and closed cooling systems

Description

Eurol Coolant -36 has especially been developed for open and closed cooling systems, according to modern requirements of the European car manufacturers. This coolant can also be used for heat transfer systems and central heating installations.

Eurol Coolant -36 prevents from scale formation, corrosion, foam-building, sludge formation and leakage. The product does not affect rubber, plastics, metals, aluminum or its alloys.

Eurol Coolant -36 provides a permanent, guaranteed protection against freezing up to -36 °C and has to be used undiluted. Never top-up with water.

Eurol Coolant -36 is nitrite, amine and phosphate free.

Specifications

Performance level

BS 6580

ASTM D3306

Physical properties

Colour	Blue	
Density at 20°C	1.064 kg/l	ASTM D 1298
Flash point	111 °C	ASTM D 93
Frost protection	-36 °C	ASTM D 1177

E504105

Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com