



Quality is in our nature

Coolants & screenwash - Cooling fluids

Eurol Coolant -36°C GLS 13

Longlife Coolant VW-TL 774 J (G13)

Description

Eurol Coolant -36 GLS 13 is specially developed for the new generation cooling systems of V.A.G. (Audi, Volkswagen, Skoda, Seat) and meets the Volkswagen VW-TL 774 J (G13) specification.

The composition of the product is different compared to other coolants, results obtained with a refractometer can be different causing an incorrect frostprotection.

Eurol Coolant -36 GLS 13 is based on glycols and organic inhibitors. This gives an excellent protection for metals in the cooling system against corrosion, specially magnesium- and aluminum alloys. Furthermore, the composition prevents scale formation and provides excellent protection against cavitation.

Eurol Coolant -36 GLS 13 is to be used undiluted, so never top-up with pure water. Eurol Coolant -36 GLS 13 provides a frost-protection down to -36°C. Life-time of the product is 5 years or 650.000 Km for trucks or 250.000 Km for passenger cars, depending on which situation occurs first.

Eurol Coolant -36 GLS 13 is compatible with traditional coolants of traditional quality.

Specifications

Performance level

VW TL-774 J (G13)

Physical properties

Colour	Pink	
Density at 20°C	1.083 kg/l	ASTM D 1298
Flash point	111 °C	ASTM D 93
Frost protection	-36 °C	ASTM D 1177

E504149

Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com