



Quality is in our nature

Greases - Aerosols

# Eurol Copper Grease spray

Protects metal against seizure caused by corrosion and chemical attack

## Description

Eurol Copper Grease Spray:

- is a multi-purpose sprayable grease with a wide temperature range that reduces wear on parts that are subjected to extreme pressure. To encounter pitting, thread deformation and galling due to corrosion and chemical exposure.
  - is formulated with a high quality bentonite grease with solid material copper.
  - is widely usable, and can be used for wheel nuts, exhaust, threads of spark plugs, bolts and nuts.
  - is not suitable for ABS and ASR brake systems
- Eurol Copper Grease Spray is water resistant and offers good resistance to high pressure. It also provides protection against corrosion and provides a good electrical conductivity.

Eurol Copper Grease Spray keeps for 3 years in an unopened can, when stored in a cool and dry place at temperatures between +5°C and +25°C.

Eurol Copper Grease Spray should be properly shaken before use.

Only use Eurol Copper Grease Spray in well-ventilated places.

## Physical properties

Flash point	-20 °C	ASTM D 93
-------------	--------	-----------

E701130

Version 1.0, 16-02-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com