



Quality is in our nature

Technical fluids - Aerosols

Eurol Chain Lube Spray Cross & Off Road

High performance chain spray for cross- and offroad applications

Description

Eurol Chain Lube Spray Cross & Off Road is a chain spray with Triple-Tech additive technology, especially developed for chains operating in dusty conditions. Eurol Chain Lube Spray Cross & Off Road has a high protection against wear, providing a long and durable protection of the sprockets and the chain.

Eurol Chain Lube Spray Cross & Off Road has an excellent penetrating ability, ensuring that the pins in the chain, as well as the bushings, receive proper lubrication, allowing for a supple chain, even after being subjected to dust and dirt.

To be able to offer the performance of the Eurol Chain Lube Spray Cross & Off Road over a longer period of time, the spray has an excellent adherence to the chain. This allows the spray to stay in place, regardless of the weather.

The Eurol Chain Lube Spray Cross & Off Road provides a protective coating to the outside of the chain, whilst the

inside of the chain is lubricated through the use of creeping additives. By applying a coating to the outside of the chain, the chain spray offers corrosion protection, keeping the chain free from rust.

Eurol Chain Lube Spray Cross & Off Road is available in a sturdy 400 ml aerosol can for easy application.

To apply the product, clean the chain, apply a thin film of Eurol Chain Lube Spray Cross & Off Road to the chain and leave to work for 30 minutes. Remove any excess material with a dry cloth.

Physical properties

Colour	Green	
Density at 20°C	0.899 kg/l	ASTM D 1298
Flash point	-20 °C	ASTM D 93

E701314

Version 1.0, 11-02-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com