



Quality is in our nature

Additives - Radiator

Eurol Radiator Sealer

Radiator additive aimed at sealing leakages

Description

Eurol Radiator Sealer is developed to protect from leaks in the head gasket, heater core, radiator, heater matrix, freeze plug, water pump casing. Eurol Radiator Sealer also prevents water leaking where plastic tanks are connected to the radiator. In the case of a radiator leak, a leak can cause your car engine to overheat, shut down or seize up.

Eurol Radiator Sealer will postpone a repair for about a few months (up to one year) of radiators with all water/glycolbased cooled engines including cars, motorbikes, commercial vehicles, and agricultural machinery. If the leak is in a plastic section of the radiator or heater core, then you have to replace it.

For preventive maintenance and a good condition of the cooling system, Eurol Radiator Sealer can be used once a year to prevent leakage and subsequent environmental pollution.

When using Eurol Radiator Sealer, no draining or flush of

the cooling system is required because it contains an antifreeze compatible formula that can be used with all types of antifreeze.

The 250ml bottle of Eurol Radiator Sealer is recommended for use in 6L to 12L of coolant. Add the additive to your radiator, run the car for approximately 10 minutes to thoroughly coat the radiator and allow the car to sit at least a few hours so that the radiator sealant can set up properly.

Radiator Sealer products work to a limited extent: keep in mind, it stops the leak (clogs up a pin hole) for small holes. For larger leaks, repair or replacement is necessary.

Users should consult the Material Safety Data Sheet of Eurol Radiator Sealer for information about storage and shelf life. Please ask Eurol Research & Development if any further information is required.

Physical properties

Colour	Brown
--------	-------

E802317

Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com