



Quality is in our nature

Greases

Eurol Copper Grease

Lubrication of tap and threaded ends, manifolds, wheel nuts and ovens

Description

Eurol Copper Grease lead-free has been especially formulated from modified clay (unmeltable bentone) and selected, high performance solid raw materials like copper, graphite and aluminium as well as anti-corrosion and anti-oxidation inhibitors.

tightening bolts. Lubricated parts are being sealed from the atmosphere.

Eurol Copper Grease lead-free is an 'anti-seize assembly compound'. It offers long-lasting protection against corrosion and harmful, external chemical reactions. It is not washed out by (salt) water.

Eurol Copper Grease lead-free is recommended for lubrication of taps, threaded fasteners, manifolds, battery clamps, wheel nuts, ovens and the back of brake pads to prevent from twisting and friction. Dismantling of sealings and threaded components is simplified, even if they have been exposed to high temperatures, corrosive conditions or high loads over a long period.

Eurol Copper Grease lead-free smoothens the surface and prevents from metal-to-metal contact when

Physical properties

Colour	Brownish	
NLGI consistency	3	
Thickener type	Bentone	
Base Oil Type	Paraffin	
Base oil viscosity	210 cSt	ASTM D 445
4-ball weld load	200	ASTM D 2596
Operating temperature	-40 - 1100 °C	

Available in 100G - 400G - 600G - 5KG - 18KG - 50KG - 185KG

E901220
Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com